

AT37/41/48 M/P



FOR NEW EQUIPMENT SALES, CALL
800.958.2555
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**[®]
TELESCOPIC ARTICULATING
AERIAL DEVICE

AT37/41/48 M/P

FEATURES

- Altec ISO-Grip®System
- 4-Function, Single Handle Upper Control
- Telescopic/Articulating Aerial Device
- Compensated Articulating Arm
- Hydraulic Boom Extension
- Insulated, ANSI Category C, 46 kV and Below
- Continuous Rotation
- Platform, Single 1-Man 24 x 30 x 42 in (610 x 762 x 1067 mm)
- Hydraulic Platform Leveling
- Platform Capacity – 400 lb (181 kg) with 180° Rotator
- Full Pressure, Open Center Hydraulic System
- Emergency Stop Valves at Upper and Lower Control Stations
- Tool Circuit at Platform
- Back-up Alarm
- Outrigger Motion Alarm and Outrigger Interlocks

OPTIONS

- ISO-Boom offering Category C Isolation w/Boom Retracted (AT41M/P Only, Not Required on AT48M/P)
- Altec ARM Jib offering Jib Capacities to 1100 lb (499 kg)
- 2-Man End Mounted Platform with 180° Platform Rotation and up to 600 lb (272 kg) capacity
- 24" Platform Elevator
- Lighting Package for Platform Controls
- Engine Start/Stop
- Manual Throttle Control
- Phase Lifting Jib Attachment and Accessories
- Attachment for Removal of ARM Jib

Recommended safety equipment, available through Altec Supply, include a platform liner, fall protection system, wheel chocks and outrigger pads.

CONFIGURATIONS

SPECIFICATIONS	AT37M/P	AT41M/P	AT48M/P
Ground to Bottom of Platform @ Reach From Centerline	37.1 ft (11.31 m) 6.9 ft (2.11 m)	40.8 ft (12.45 m) 7.3 ft (2.21 m)	47.5 ft (14.48 m) 6.7 ft (2.04 m)
Maximum Side Reach:			
End-Mount	26.3 ft (8.02 m)	30.1 ft (9.16 m)	31.2 ft (9.51 m)
@ Platform Height	17.3 ft (5.27 m)	17.3 ft (5.27 m)	21.9 ft (6.67 m)
Stowed Travel Height*	10.7 ft (3.26 m)	10.7 ft (3.26 m)	10.7 ft (3.26 m)
Platform Capacity	400 lbs (181 kg)	400 lbs (181 kg)	400 lbs (181 kg)
Lower Boom Articulation	-25 to 85°	-25 to 85°	-25 to 85°
Articulating Arm Articulation	-3 to 82°	-3 to 82°	-3 to 82°
Rotation	Continuous	Continuous	Continuous

*Based on a 40 in (1016 mm) chassis frame height.

ANSI A92.2-2015 Compliant

General Specifications Key:

The Letter 'M' in the Model Name Indicates the Material Handling Configuration.
The Letter 'P' in the Model Name Indicates the Personnel Configuration.



24" PLATFORM ELEVATOR OPTIMIZES
OPERATOR REACH WITHIN WORK ZONE

ALLOWS EASY ACCESS TO PLATFORM FROM GROUND



LIGHTING PACKAGE TO OPTIMIZE VISION/SAFETY FOR NIGHT VISION WORK



JIB ROTATION RELEASE LEVER PROVIDES EASY PINNING OF ARM JIB



For more complete information on Altec products and services, visit us on the web at www.altec.com. Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Altec® and the Altec logo are registered trademarks of Altec Inc. in the United States and various other countries and may not be used without permission.

© 2025 Altec Inc. All Rights Reserved. AI_AT374148MPOS_101525



NEW EQUIPMENT SALES | 800.958.2555 | SALES@ALTEC.COM | ALTEC.COM